

## DRIVER SPECIFICATIONS

<p><b>Parameter</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>F<sub>o</sub></td> <td>700Hz ± 20%</td> </tr> <tr> <td>SPL<sub>o</sub> ( 1m/1w)</td> <td>91dB±3dB</td> </tr> <tr> <td>Q<sub>ts</sub></td> <td>/</td> </tr> <tr> <td>V<sub>as</sub></td> <td>/</td> </tr> <tr> <td>Rated Impedance</td> <td>6 Ω ± 15%</td> </tr> <tr> <td>Rated power</td> <td>20 Watts</td> </tr> <tr> <td>Long Term Power</td> <td>40 Watts</td> </tr> <tr> <td>Fr. Response</td> <td>700Hz~32KHz</td> </tr> <tr> <td>Shielding</td> <td>YES</td> </tr> </table>	F <sub>o</sub>	700Hz ± 20%	SPL <sub>o</sub> ( 1m/1w)	91dB±3dB	Q <sub>ts</sub>	/	V <sub>as</sub>	/	Rated Impedance	6 Ω ± 15%	Rated power	20 Watts	Long Term Power	40 Watts	Fr. Response	700Hz~32KHz	Shielding	YES	<p style="text-align: center;"><b>SPL vs Freq</b></p>
F <sub>o</sub>	700Hz ± 20%																		
SPL <sub>o</sub> ( 1m/1w)	91dB±3dB																		
Q <sub>ts</sub>	/																		
V <sub>as</sub>	/																		
Rated Impedance	6 Ω ± 15%																		
Rated power	20 Watts																		
Long Term Power	40 Watts																		
Fr. Response	700Hz~32KHz																		
Shielding	YES																		
<p><b>Structure of Driver</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Diaphragm</td> <td>Upgraded Mod. Silk</td> </tr> <tr> <td>Frame/panel</td> <td>Plastic</td> </tr> <tr> <td>Magnet Diameter</td> <td>φ24.5mm</td> </tr> <tr> <td>Magnet Weight</td> <td>12.4g/0.44oz</td> </tr> <tr> <td>Voice Coil</td> <td>ASVφ25.4mm</td> </tr> <tr> <td>Weight</td> <td>85g</td> </tr> </table>	Diaphragm	Upgraded Mod. Silk	Frame/panel	Plastic	Magnet Diameter	φ24.5mm	Magnet Weight	12.4g/0.44oz	Voice Coil	ASVφ25.4mm	Weight	85g							
Diaphragm	Upgraded Mod. Silk																		
Frame/panel	Plastic																		
Magnet Diameter	φ24.5mm																		
Magnet Weight	12.4g/0.44oz																		
Voice Coil	ASVφ25.4mm																		
Weight	85g																		
<p><b>Picture</b></p>																			